








ISO2768-M MEDIUM																							REV	ECN	DATE	APPROVED
	LENGTH/ DIAMETER	0.5-6	>6-30	>30-120	>120-400	>400-1000	>1000-2000	>2000-4000	RADIUS/ CHAMFER	0.5-3	>3-6	>6	ANGLE (shorter side length)	0-10	>10-50	>50-120	>120-400	>400	C	18-038	3/21/18	YC				
	TOLERANCE	±0.1	±0.2	±0.3	±0.5	±0.8	±1.2	±2	TOLERANCE	±0.2	±0.5	±1	TOLERANCE	±1°	±0.5°	±0.3°	±0.15°	±0.1°	D	20-060	2020-06-29	YC				



Electrical Data:
Code: Incremental with sin/cos interface
Number of pulses: 2048
Operating Voltage: 5 ±10% VDC
No-load supply current: 150mA max
Output Signals: sin/cos 1Vpp
Maximum Response Frequency: 180 kHz
Mechanical Data:
Weight: 200g typ.
Dimensions:
Outside Diameter with cover: 53.3mm; Mounting depth: MAX 40MM
Material:
Bearing housing: aluminium;
Cover: aluminium;
Shaft: Brass
Shaft Diameter: 12.7mm
Mating Shaft Runout: ±0.1mm max.
(Includes shaft perpendicularity to mounting surface)
Mating Shaft Axial movement: max. ±0.4mm
Max. Velocity: 6000 RPM,
Environmental:
Operating Temperature: -20°C to +100°C
Storage Temperature: -40°C to +120°C
Shock: 100 Gs for 11 msec duration
Vibration: 10 Gs at 5 to 2000 Hz
Relative Humidity: 95% non-condensing
Enclosure Rating: IP 40 (Cable needs to be oriented downwards)



Connector		
PIN	Color	Function
1a	BRN	C-
1b	GRY/PNK	5V
2a	YLW	A-
2b	BLK	D+
3a	GRN/BRN	Sensor 0V
3b	BLU	B+
4a	PNK	R-
4b	GRY	R+
5a	RED	B-
5b	WHT/GRN	GND
6a	VIO	D-
6b	GRN	A+
7a	RED/BLU	Sensor Up
7b	WHT	C+

TOLERANCES UNLESS INDICATED:			UNITS: mm		TITLE OUTLINE & SPEC, RS20 OPT08			
.XXX	.XX	ANGLES	MATERIAL:		FILE NAME:	SCALE:	COMPLIANCE REQUIRED	
±	±	±	FINISH:		703058-0010	/	☐ UL	☐ CSA ☐ CE ☐ TUV
/	/	/			DRAWN:	DATE:	☐ FCC ☐ VCCI ☒ RoHS ☒ REACH	
					DEVIN	2017-08-28	PRO/E MODEL: 703058-0010	
					CHECKED:	DATE:	APPLICATION: RS20 OPT08	
					DEVIN	2017-08-28	DRAWING NUMBER	
					RELEASED:	DATE:	703058-0010	
					YC	2017-08-28		

© 2017 D.T.C. "C" SIZE
HENGSTLER